



Available on
GeM
Government
e Marketplace



Enterprise Series

IR Dome Camera (Outdoor)

MODEL: GDC-OF-A

GDC-OF-A



Available on

GeM
Government e Marketplace

Applications

Educational Institutes, Hospital, Offices

Shops, Malls and other market places

Airport, Railway stations etc.

IR Dome Camera (Outdoor)



Technical Specifications

Model	GDC-OF-A
Signal System	PAL
Effective Pixels	1/3", 1M Pixels
Horizontal Resolution	HD (1280 x 720 pixel)
Lens Type	3.6 mm (focal length)
Signal to noise ratio	> 50 db
Video Output Signal	1Vp-p composite (75 ohms)
Scanning frequency-(v)	15.625 KHz (H) and 50 Hz (V)
Auto Exposure	Yes
Shutter Speed	1/50s~1/100,00s
Minimum illumination	0.01 lux
Video Streaming	720P @25 fps
Video Output	1-Channel BNC video output
IR	IR Range of 20 M, Smart IR
Signal Process	Digital Signal Process
Scanning System	2:1 interlaced Progressive
Auto Gain Control	Yes
Back Light Compensation	Yes
White Balance	Yes
Day and Night	Yes
Operating Temperature	-10°C to 50°C & 40°C at 95% RH
Power Source	12V DC Adapter
Power Consumption	Max 2.5W
On screen Display	OSD on Display/ Monitor in English
Housing-Outdoor	Plastic Construction with IP 66
Certifications	CE, FCC, RoHs
Weight	200 gm
Dimension	85 x 65 mm

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ✉ 0120-4051827 📧 info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com