

3000 ANSI Lumens
2000:1 Contrast Ratio
Upto 6000 Hours Lamp Life
Auto Digital Keystone Correction
6-Segment Color Wheel



GD30X

PORTABLE MULTIMEDIA PROJECTOR

Special Features:

- Instant Shut Down
- Dynamic Lamp Power Control
- Closed Caption
- Wall Screen (Beige/Blue/Green/Pink/Black Board/White Board)
- Top Access Lamp
- HDMI and Dual PC Inputs
- Network Control and Management with Projector View Global + Software
- Visual PA Message System
- 10W Audio Speaker Audio Mix Feature
- Lamp Hour Counter - Built in
- 12 Language OSD
- Power Consumption for Stand by: less than 1 W
- Chain Lock Bar

WiFi Presentation System

- Plug and show
- 4 to 1 Split screen wireless projection
- IEEE 802.11b/g compliant
- Real Time Video Streaming up to XGA



Dazzle your

AUDIENCE

with a

MESMERIZING PRESENTATION

INSPIRE, TEACH, COMMUNICATE & MOTIVATE

SPECIFICATIONS

FEATURE	GD 30X
Display Technology	0.55" 1-Chip DMD, 12deg. LVDS, DDP2230
Resolution	Native XGA (1024 x 768)
Brightness	3000 ANSI Lumens
Contrast Ratio	2000 : 1
Zoom / Focus	6-Segment Color Wheel (R / G / B / W / Y/ C)
Color Wheel	Manual Focus and Zoom Lens (Zoom Ratio 1.2 : 1)
Wall Color Support	Beige / Blue / Green / Pink / Black Board / White Board
Projection Lens	f=18.4 ~ 22.0 mm, F=2.5-2.8, (3.3-4.0m@100")
Picture Size	40 - 300 inches diagonal
Source Lamp	190W (Shut-off Time 6000 hrs)
PC Compatibility	640 x 480 - 1024 x 768 + Compressed 1280 x 1024 Sync on Green Available
Video Compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component Video 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i (1125i 60Hz), 1080i (1125i 50Hz)
Input Terminals	RGB: mini D-sub 15pin x 2 Audio: Stereo mini jack (ø3.5mm) x 2 (One for PC, another one for Video) Video: RCA x 1 + S-VIDEO x 1 Digital: HDMI x 1 VideoAudio: RCA jack (L/R) x 1
Output Terminals	RGB:mini D-sub 15pin x 1 Audio:Stereo mini jack (ø3.5mm) x 1
Communication Terminals	RS232C: mini DIN 8 pin x 1 LAN (RJ-45): x 1
Scanning Rate	[H] 15-80 kHz, [V] 50-85 Hz, [Dot Clock] Max. 110 MHZ
Audio Speaker	10W
Hand Remote Unit	Full Mouse Control
Power Consumption	330 W
Dimension	325 x 118 x 251 mm
Weight	3.3 Kg
Power Requirements	AC 100-240V, 50/60 Hz
Fan Noise	33 dBA (Low mode: 28 dBA)
Supplied Accessories	AC Power Cable, VGA Cable, Remote Control (with Battery), WiFi Presentation Dongle, Carrying Case
Warranty	1 - Year Standard Warranty

AVAILABLE ON
DGS&D RATE CONTRACT

Technical Support
Toll Free: 1800111199
E-mail: service@globusinfocom.com



Globus Infocom Ltd.

C-1/2, Safdargunj Development Area

New Delhi - 110016

Tel/Fax: 011-26964810

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com