




Available on
GeM
Government
e Marketplace



4 Channel Digital Video Recorder

MODEL: GC-DVR-4

Key Features

- Support HDCVI/ Analog/ IP Video input
- All channel 720P Real time Recording
- Audio and Video ports to receive live audio recording and playback of recorded audio and video of camera
- Copy recorded files to external Hard disk or memory card through USB Port
- Recorded video format compatible with all standard media players
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 4TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro

Application Areas

Educational Institutes, Hospital, Offices

Shops, Malls and other market places

Airport, Railway stations etc.



Available on
GeM
Government e Marketplace

4 Channel Digital Video Recorder

Model: GC-DVR-4

Technical Specifications

| | |
|---------------------|--|
| User Interface | GUI |
| Processor | Embedded processor |
| Operating System | Embedded Linux |
| Two-way Talk | Audio input/output channel 1 |
| Video Input | 4 channel, BNC |
| Video Output | 1 HDMI, 1 VGA |
| Video Standard | Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s), HDCVI: 1080P/720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera |
| Video Compression | H.264 / MPEG |
| Video Resolution | 1920 x1080, 1280 x 1024, 1280 x 720, 1024 x 768 |
| Video Recording | Main Stream: 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF (1~25/30fps) |
| Video Display Split | 42739 |
| Audio Compression | G.711 |
| Audio Input | 1 channel, RCA |
| Audio Output | 1 channel, RCA |
| Hard Disk | 1 SATA port, up to 4TB |
| Trigger Events | Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips |
| Recording Mode | Manual, Schedule(Regular(Continuous), MD), Stop |
| Search Mode | Time/Date, MD & Exact search (accurate to second) |
| Playback | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom |
| Backup Mode | USB Device |
| Interface Ports | 1 HDMI, 1 VGA, 1 USB2.0, 1 RS485 |
| Record Interval | 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec |
| Max User Account | 128 users |
| Ethernet | RJ-45 port (10/100M) |
| Protocols | HTTP, IPv4/IPv6, TCP/IP, RTSP, SMTP, DHCP, DNS, DDNS, IP Filter, P2P, ONVIF Version 2.4 conformance |
| Power Supply | DC12V/1.5A |
| Power Consumption | 10W (without HDD) |
| Working Temp | -10° ~ +55°C / 10 ~ 90% RH / 86~106kpa |
| Dimension | 260 mm x 220 mm x 40 mm |
| Weight | 0.75KG (without HDD) |
| Special Features | Motion Detection, Video Loss Support, Camera Blank, Smart Phone Support |

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ✉ 0120-4051827 📧 info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com